PRODUCT CATALOGUE / ENGLISH EDITION

Mowers.

Choose the cut.
Match the tractor.

Sickle-bar, rotary drum and rotary disc mowers for grass and forage work. Compare the cutting system, working width and tractor requirement for your market.

03
CUTTING SYSTEMS

11
MODEL REFERENCES

Every need. One partner. From A to Z.



Rotary drum mower



Sickle-bar mowers



Rotary disc mowers

Choose the mower around the job.

Compare the listed cutting widths and tractor requirements, then open the model page for the complete specification.

Cutting system	Working width choices	Tractor power (hp)	Product page
Sickle-bar mowers **A2ZSB / A2ZDB references**	160 or 170, 175, or 205 cm	35/40; 40/45; 50/55	03 / SICKLE BAR
Rotary drum mowers **A2ZAT-MR references**	1.25, 1.35, 1.65, 1.85 or 2.50 m	25, 35, 45, 60 or 70	04 / DRUM
Rotary disc mowers **A2ZAT-MD references**	1.65, 2.05 or 2.45 m	40-50; 50-60; 60-80	05 / DISC

THREE POINTS FOR A BETTER MACHINE MATCH

01 / Crop & field

Crop type, terrain and desired cutting width.

02 / Tractor

Available power, PTO and linkage arrangement.

03 / Supply package

Quantity, destination and required equipment.

Sickle-bar mowers.

A2ZSB-BM / A2ZDB-HD1 / A2ZDB-HD2



Cutter-bar arrangement

Representative family photograph.

Match the bar to the tractor.

Compare the cutting width, weight and work speed to match the cutter-bar package to your tractor. The 160 or 170 cm choice belongs to A2ZSB-BM.

KEY BENEFITS

- **Width choice:** 160 or 170, 175, or 205 cm.
- **Lighter reference:** 150 kg for A2ZSB-BM.
- **Work speed:** Model-specific figures below.

FIELD SETUP



Cutterbar at the field edge.

TECHNICAL SELECTION

A2Z model code	A2ZSB-BM	A2ZDB-HD1	A2ZDB-HD2
Working width (cm)	160 or 170	175	205
Weight (kg)	150	230	250
Work speed (km/h)	8-10	12-15	12-15
Tractor power (hp)	35/40	40/45	50/55

Field-edge setup shown. Photographs represent the family; cutting width and equipment follow the selected model.

Rotary drum mowers.

Five working-width choices with tractor PTO drive and model-specific power requirements.



165 configuration - belt housing and drum cover

IN THE FIELD



Drum mowing in the field.

Product: two-drum 165. Field photo: family view. The 250 reference uses four drums.

Two drums. Or four.

A 540 rpm tractor PTO drives the belt-and-pulley transmission. Compare five widths and their tractor requirements. The 250 reference steps up to four drums and twelve blades.

KEY BENEFITS

- **PTO input:** 540 rpm tractor drive.
- **Cutting layout:** Two or four drums, by model.
- **Power matching:** 25 to 70 hp across the listed references.

WATCH THE 165 FIELD VIDEO

TECHNICAL SELECTION

PTO input: 540 rpm | Drum speed: 1,920 rpm

A2Z model code	A2ZAT-MR 125	A2ZAT-MR 145	A2ZAT-MR165	A2ZAT-MR185	A2ZAT-MR250
Working width (mm)	1250	1350	1650	1850	2500
Overall length (mm)	2425	2625	2925	3430	3775
Overall width (mm)	1050	1090	1150	1175	1250
Overall height (mm)	1100	1100	1100	1150	1150
Blades (pcs)	6	6	6	6	12
Drums (pcs)	2	2	2	2	4
Weight (kg)	285	315	345	400	510
Tractor power (hp)	25	35	45	60	70

The 145 model reference is listed with a working width of 1,350 mm in the source specification.

Rotary disc mowers.

Three cutting widths with a separate disc count, blade count and tractor requirement for each reference.



Disc cutterbar - guard raised for product display

IN THE FIELD



Disc mowing in standing forage.

Product and field photographs show the family; width, disc count and equipment follow the selected model.

Four, five or six discs.

Choose a PTO-driven disc cutting system for grass and forage. Each width has its own disc-and-blade arrangement. Compare the complete machine dimensions, weight and tractor power before selecting the package.

KEY BENEFITS

- **Width choice:** 1.65, 2.05 or 2.45 m.
- **Cutting layout:** Two blades per disc in every reference.
- **Tractor match:** Model-specific 40-50, 50-60 or 60-80 hp.

TECHNICAL SELECTION

Disc speed: 3,200 rpm | Disc and blade counts are listed separately below

A2Z model code	A2ZAT-MD 165	A2ZAT-MD 205	A2ZAT-MD 245
Working width (mm)	1650	2050	2450
Overall length (mm)	2500	2625	2950
Overall width (mm)	1050	1200	1400
Overall height (mm)	1050	1150	1250
Blades (pcs)	8	10	12
Discs (pcs)	4	5	6
Weight (kg)	670	750	820
Tractor power (hp)	40-50	50-60	60-80

A clear specification. A reliable supply partner.

A2ZEXIMCO connects international machinery buyers with sourcing and export supply from Türkiye.

SEND US YOUR MOWER REQUIREMENT

Cutting system & model

A2Z model code and required working width.

Crop & tractor

Crop, field conditions, tractor power and PTO.

Machine package

Required equipment and spare-parts needs.

Quantity & destination

Units, delivery country and destination port.

HOW A2Z SUPPORTS YOUR ORDER

Configuration review

Align the machine specification with your requirement.

Sourcing & export coordination

Coordinate the offer, supply and export arrangements.

Pre-loading review

Factory photographs and videos support the loading review.

Parts & after-sales support

Discuss parts planning and support for the selected machine.

REQUEST YOUR MACHINE QUOTATION

agriculture@a2zeximco.com

+90 553 002 19 52

a2zeximco.com/en/catalogs

Final specifications and included equipment follow the agreed quotation. Photographs represent product families.