

SECTION 10

MIXER FEEDERS

Electric and PTO-driven vertical feed-mixing solutions for consistent ration preparation and efficient livestock feeding.

7 PRODUCT FAMILIES

TECHNICAL DATA | MODEL OPTIONS | APPLICATION OVERVIEW

MIXER FEEDERS

Electric and PTO-driven vertical feed-mixing solutions for consistent ration preparation and efficient livestock feeding.

RANGE AT A GLANCE

07

PRODUCT FAMILIES

- Heavy Duty Electric Vertical Feed Mixer Machine 4 m3 to 8 m3
- Heavy Duty PTO Vertical Feed Mixer Machine 4 m3 to 8 m3
- Electric Vertical Feed Mixer Machine 1.5 m3 to 3 m3
- PTO Vertical Feed Mixer Machine 1.5 m3 to 3 m3
- Electric Vertical Feed Mixer Machine 2 m3-3 m3
- Stationary Vertical Feed Mixer Machine 1 m3-2 m3
- Vertical Feed Mixer 1 m3 to 2 m3

BUILT FOR B2B SUPPLY

- Importers and distributors
- Agricultural machinery dealers
- Professional farms and contractors
- Project and fleet requirements
- Long-term supply cooperation

MATCHED SELECTION

Models and options matched to your field and tractor requirements.

EXPORT COORDINATION

Clear quotations, documentation and shipment communication.

LONG-TERM SUPPORT

Factory coordination, spare parts availability and after-sales follow-up.

REQUEST A MATCHED EXPORT QUOTATION

Share the required model, quantity, tractor power and destination. We will coordinate the suitable configuration and commercial offer.

MIXER FEEDERS

HEAVY DUTY ELECTRIC VERTICAL FEED MIXER MACHINE 4 M³ TO 8 M³



PRODUCT OVERVIEW

Heavy duty electric vertical feed mixer for livestock and dairy farms. Available in 4 m³, 5 m³, 6 m³ and 8 m³ capacities for homogeneous daily feed preparation. The A2Z-ELVFM-H Series Heavy Duty Electric Vertical Feed Mixer Machine is designed for medium and large-scale livestock farms that require efficient, homogeneous and high-capacity daily feed preparation. With its electric-driven vertical mixing system, this series provides a practical solution for preparing balanced feed rations in fixed working areas.

TECHNICAL SPECIFICATIONS

Model / Specification	A2Z-ELVFM-H4000	A2Z-ELVFM-H5000	A2Z-ELVFM-H6000	A2Z-ELVFM-H8000
Capacity	4 m ³	5 m ³	6 m ³	8 m ³
Auger Type	Vertical	Vertical	Vertical	Vertical
Number of Knives	8	9	9	12
Base Thickness	10 mm	14 mm	15 mm	15 mm
Wall Thickness	4 mm	5 mm	5 mm	5 mm
Tank Dimensions	2210 × 1430 × 1805 mm	2450 × 2000 × 1610 mm	2800 × 2000 × 1800 mm	3060 × 2300 × 1900 mm
Number of Augers	1	1	1	1
Working Speed	540 rpm	540 rpm	540 rpm	540 rpm
Weight	1350 kg	1780 kg	2050 kg	2630 kg
Minimum Power	30 HP	35 HP	55 HP	60 HP



MIXER FEEDERS

HEAVY DUTY PTO VERTICAL FEED MIXER MACHINE 4 M³ TO 8 M³



PRODUCT OVERVIEW

Heavy duty PTO vertical feed mixer for livestock and dairy farms. Available in 4 m³, 5 m³, 6 m³ and 8 m³ capacities for efficient daily feed preparation. The A2Z-PVFM-H Series Heavy Duty PTO Vertical Feed Mixer Machine is designed for medium and large-scale livestock farms that require efficient, homogeneous and high-capacity daily feed preparation. Powered by tractor PTO (540 rpm), this machine series offers reliable performance for mixing silage, roughage, hay and concentrated feed materials into a balanced feed ration.

TECHNICAL SPECIFICATIONS

Model / Specification	A2Z-PVFM-H4000	A2Z-PVFM-H5000	A2Z-PVFM-H6000	A2Z-PVFM-H8000
Capacity	4 m ³	5 m ³	6 m ³	8 m ³
Auger Type	Vertical	Vertical	Vertical	Vertical
Number of Knives	8	9	9	12
Base Thickness	10 mm	14 mm	15 mm	15 mm
Wall Thickness	4 mm	5 mm	5 mm	5 mm
Tank Dimensions	2210 × 1430 × 1805 mm	2450 × 2000 × 1610 mm	2800 × 2000 × 1800 mm	3060 × 2300 × 1900 mm
Number of Augers	1	1	1	1
PTO Speed	540 rpm	540 rpm	540 rpm	540 rpm
Weight	1350 kg	1780 kg	2050 kg	2630 kg
Minimum Tractor Power	30 HP	35 HP	55 HP	60 HP



MIXER FEEDERS

ELECTRIC VERTICAL FEED MIXER MACHINE 1.5 M³ TO 3 M³



PRODUCT OVERVIEW

Electric vertical feed mixer for livestock and dairy farms. Available from 1.5 m³ to 3 m³ for efficient and homogeneous daily feed preparation. The A2Z-ELVFM Series Electric Vertical Feed Mixer Machine is designed for livestock farms that require efficient, homogeneous and practical daily feed preparation. Developed as an electric motor-driven feeding solution, this series is suitable for preparing balanced feed mixtures in fixed working areas without the need for a tractor.

TECHNICAL SPECIFICATIONS

Model / Specification	A2Z-ELVFM-150 OF	A2Z-ELVFM-200 OF	A2Z-ELVFM-200 OT	A2Z-ELVFM-250 OF	A2Z-ELVFM-250 OT	A2Z-ELVFM-300 OT
Capacity	1.5 m ³	2 m ³	2 m ³	2.5 m ³	2.5 m ³	3 m ³
Auger Type	Vertical	Vertical	Vertical	Vertical	Vertical	Vertical
Number of Knives	7	7	7	7	7	8
Base Thickness	8 mm	8 mm	8 mm	8 mm	8 mm	10 mm
Wall Thickness	3 mm	3 mm	3 mm	3 mm	3 mm	4 mm
Tank Dimensions	1630 × 1255 × 1350 mm	1800 × 1220 × 1400 mm	1800 × 1220 × 1400 mm	1925 × 1290 × 1550 mm	1925 × 1290 × 1550 mm	2080 × 1430 × 1600 mm
Number of Augers	1	1	1	1	1	1
Working Speed	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm
Weight	600 kg	750 kg	900 kg	850 kg	1000 kg	1200 kg
Minimum Power	20 HP	25 HP	25 HP	25 HP	25 HP	30 HP



PTO VERTICAL FEED MIXER MACHINE 1.5 M³ TO 3 M³



PRODUCT OVERVIEW

PTO vertical feed mixer for livestock and dairy farms. Available from 1.5 m³ to 3 m³ with 540 rpm tractor PTO operation. The A2Z-PVFM Series PTO Vertical Feed Mixer Machine is designed for livestock farms that require efficient, homogeneous and practical feed preparation. Powered by tractor PTO, this vertical feed mixer provides reliable performance for mixing silage, roughage, hay and concentrated feed materials in daily feeding operations.

TECHNICAL SPECIFICATIONS

Model / Specification	A2Z-PVFM-1500F	A2Z-PVFM-2000F	A2Z-PVFM-2000T	A2Z-PVFM-2500F	A2Z-PVFM-2500T	A2Z-PVFM-3000T
Capacity	1.5 m ³	2 m ³	2 m ³	2.5 m ³	2.5 m ³	3 m ³
Auger Type	Vertical	Vertical	Vertical	Vertical	Vertical	Vertical
Number of Knives	7	7	7	7	7	8
Base Thickness	8 mm	8 mm	8 mm	8 mm	8 mm	10 mm
Wall Thickness	3 mm	3 mm	3 mm	3 mm	3 mm	4 mm
Tank Dimensions	1630 × 1255 × 1350 mm	1800 × 1220 × 1400 mm	1800 × 1220 × 1400 mm	1925 × 1290 × 1550 mm	1925 × 1290 × 1550 mm	2080 × 1430 × 1600 mm
Number of Augers	1	1	1	1	1	1
PTO Speed	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm
Weight	600 kg	750 kg	900 kg	850 kg	1000 kg	1200 kg
Minimum Tractor Power	20 HP	25 HP	25 HP	25 HP	25 HP	30 HP



MIXER FEEDERS

ELECTRIC VERTICAL FEED MIXER MACHINE 2 M³-3 M³



PRODUCT OVERVIEW

380V electric vertical feed mixer for livestock and dairy farms. Available in 2 m³ and 3 m³ models for efficient and homogeneous daily feed preparation. The A2Z-EVFM Series 380V Electric Vertical Feed Mixer Machine is designed for livestock farms that require homogeneous, practical and efficient daily feed preparation. With its electric-powered vertical auger system, this machine series allows silage, roughage and concentrated feed materials to be mixed quickly and evenly for daily feeding operations.

TECHNICAL SPECIFICATIONS

Model / Specification	A2Z-EVFM-2000	A2Z-EVFM-3000
Capacity	2 m ³	3 m ³
Auger Type	Vertical	Vertical
Number of Knives	16	24
Base Thickness	5 mm	8 mm
Wall Sheet Thickness	3 mm	3 mm
Tank Dimensions	2300 × 1200 × 1600 mm	2812 × 1400 × 1800 mm
Number of Augers	2	3
Weight	600 kg	800 kg
Electric Motor Power	3 HP	3 HP
Operating Voltage	380V	380V



STATIONARY VERTICAL FEED MIXER MACHINE 1 M³-2 M³



PRODUCT OVERVIEW

Stationary vertical feed mixer for cattle and livestock farms. Electric feed mixing machine with 1 m³ and 2 m³ models for homogeneous daily ration preparation. The A2Z-SVFM Series Stationary Vertical Feed Mixer Machine is designed for efficient daily feed preparation in cattle farms, dairy farms and medium-scale livestock operations. With its vertical auger mixing system, compact structure and electric motor drive, it helps prepare a homogeneous and balanced feed mixture with reduced labor and time.

TECHNICAL SPECIFICATIONS

Model / Specification	A2Z-SVFM-1000	A2Z-SVFM-2000
Capacity	1 m ³	2 m ³
Mixer Type	Stationary Vertical	Stationary Vertical
Auger Type	Vertical	Vertical
Number of Knives	4	16
Base Sheet Thickness	5 mm	5 mm
Wall Sheet Thickness	3 mm	3 mm
Tank Dimensions	1280 × 940 × 1430 mm	2300 × 1200 × 1600 mm
Number of Augers	1	2
Approx. Weight	200 kg	600 kg
Electric Motor Power	4 HP	3 HP



MIXER FEEDERS

VERTICAL FEED MIXER 1 M³ TO 2 M³



PRODUCT OVERVIEW

Vertical feed mixer for livestock farms with compact design, durable tank structure, vertical auger system and practical daily feed preparation. The A2Z VM Series Vertical Feed Mixer is designed for small and medium-sized livestock farms that need a practical, compact and reliable feed preparation solution. With its vertical auger mixing system, it helps combine silage, roughage and concentrated feed materials into a more balanced and homogeneous ration for daily animal feeding.

TECHNICAL SPECIFICATIONS

Model / Specification	A2Z-VM-1F	A2Z-VM-2F
Capacity	1 m ³	2 m ³
Auger Type	Vertical	Vertical
Number of Knives	4	16
Base Thickness	5 mm	5 mm
Wall Thickness	3 mm	3 mm
Tank Dimensions	1280 × 940 × 1430 mm	2300 × 1200 × 1600 mm
Number of Augers	1	2
Weight	200 kg	600 kg
Electric Motor Power	4 HP	3 HP





LET'S BUILD LONG-TERM VALUE.

From productselection to internationaldelivery, A2ZEXIMCO provides one point of coordination for agricultural machinery sourcing from Türkiye.

CONTACT & PRODUCT INFORMATION

www.a2zeximco.com

Türkiye | AgriculturalMachineryExport&GlobalSupply



Technical specifications, model availability and imagery may be updated without prior notice. Final configuration and commercial terms are confirmed in the official quotation.